



Safety Data Sheet

Oust V.O.C. Compliant

SECTION 1. IDENTIFICATION

Product Identifier	Oust V.O.C. Compliant
Other Means of Identification	Code No. 177
Recommended Use	Solvent Cleaner.
Restrictions on Use	Use only as directed according to label instructions.
Manufacturer	Leysons Products, a division of 1787528 Ontario Inc., 1366 Sandhill Drive, Ancaster, Ontario, L9G 4V5, (905) 648-7832
Emergency Phone No.	Mark Bryans, (905) 648-7832 ext 351, Monday to Friday, 8:00 AM to 3:30 PM CANUTECH, 613-996-6666, 24-hr for Emergencies involving Dangerous Goods
SDS No.	0800

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable liquid - Category 3; Skin irritation - Category 3; Eye irritation - Category 2A; Aspiration hazard - Category 1

Label Elements



Danger

May be fatal if swallowed and enters airways.

Causes skin and eye irritation.

Flammable liquid and vapour.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Hydrotreated kerosene	64742-47-8	45 - 70%		
2-Butoxyethanol	111-76-2	1-5		
Coconut Diethanolamide	68603-42-9	1-5		
Naphtha (petroleum), hydrotreated light	64742-49-0	15 - 40%		
Alcohols, C9-11, ethoxylated, liquids	68439-46-3	0.1-1.0		

Notes

Concentrations are expressed in % weight/weight.

Product Identifier: Oust V.O.C. Compliant - Ver. 1
Date of Preparation: November 13, 2024
Date of Last Revision:

SDS No.: 0800

Page 01 of 07

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

If irritation is experienced, remove person to fresh air.
Get medical advice or attention if you feel unwell or are concerned.

Skin Contact

IF ON SKIN (or hair), remove all contaminated clothing and launder before reuse.
Rinse skin with plenty of water or shower.
Call a physician if irritation develops or persists.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open.
If eye irritation persists, get medical advice or attention.

Ingestion

In case of ingestion, call a doctor or anti-poison Centre.

Most Important Symptoms and Effects, Acute and Delayed

Aspiration hazard. May irritate the respiratory system. Harmful if swallowed. May cause skin irritation on prolonged contact. May cause moderate to severe eye irritation.

Immediate Medical Attention and Special Treatment

Target Organs

Eyes, skin, respiratory system, digestive system, nervous system.

Medical Conditions Aggravated by Exposure

Asthma, skin allergies.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam.

Specific Hazards Arising from the Product

Flammable liquid.

If involved in a fire, it may generate oxides of carbon, nitrogen or ammonia if heated above its boiling point.

Special Protective Equipment and Precautions for Fire-fighters

Wear full fire fighting equipment and self contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Wear protective gloves and eye protection as a precaution.

Wear a NIOSH approved air-purifying respirator with an organic vapour cartridge.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway.

If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas.

Minimize the use of water to prevent environmental contamination.

Methods and Materials for Containment and Cleaning Up

Eliminate all sources of ignition, flames or sources of electrical discharge.

Use non-sparking tools and explosion proof equipment in the case of large spills.

Contain and/or absorb spill with commercial absorbents and then place into a suitable container for disposal.

Use ventilation adequate to keep exposures (airborne levels of fumes / vapours) below recommended exposure limits.

Product Identifier: Oust V.O.C. Compliant - Ver. 1

SDS No.: 0800

Date of Preparation: November 13, 2024

Date of Last Revision:

Page 02 of 07

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not get in eyes, on skin or on clothing.

Only use where there is adequate ventilation.

Eliminate heat and ignition sources such as sparks, open flames, hot surfaces and static discharge. Post "No Smoking" signs.

Do not breath gas/fumes/vapour/spray.

Do NOT ingest.

Keep containers tightly sealed when not in use.

Wear a NIOSH approved air- purifying respirator with an organic vapour cartridge.

Wear gloves and eye protection as a precaution.

Conditions for Safe Storage

Store in a cool dry area away from incompatible materials.

Keep out of reach of children in a tightly closed container away from food, drink and animal feed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Chemical Name	ACGIH TLV®		OSHA PEL		AIHA WEEL	
	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Hydrotreated kerosene	200 mg/m3					
2-Butoxyethanol	20 ppm		25 ppm			
Coconut Diethanolamide	Not established					
Alcohols, C9-11, ethoxylated, liquids	Not established		Not established			
Naphtha (petroleum), hydrotreated light	Not established					

Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of vapour) below the recommended exposure limits.

Use local exhaust ventilation and enclosure, if necessary, to control amount in the air.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles and face shield when contact is possible.

Skin Protection

Wear protective gloves and clothing to prevent skin contact.

Respiratory Protection

Use in well ventilated areas. In case of insufficient ventilation, wear a NIOSH approved air-purifying respirator with an organic vapour cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Appearance	Clear blue - green liquid.
Odour	Cherry
Odour Threshold	Not available
pH	Not applicable
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Boiling point/Initial boiling point	Not available
Boiling Range	Not available

Product Identifier: Oust V.O.C. Compliant - Ver. 1

SDS No.: 0800

Date of Preparation: November 13, 2024

Date of Last Revision:

Page 03 of 07

Flash Point	~ 16 °C (61 °F)
Evaporation Rate	Not available
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	Not available
Relative Density (water = 1)	Not available
Solubility	Insoluble in water; Not available (in other liquids)
Partition Coefficient, n-Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	Not available (kinematic); Not available (dynamic)

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use.

Chemical Stability

Normally stable.

Possibility of Hazardous Reactions

May catch fire.

Conditions to Avoid

High temperatures.

Freezing.

Incompatible materials.

Incompatible Materials

Strong acids (e.g. hydrochloric acid), strong oxidizing agents (e.g. perchloric acid), strong reducing agents (e.g. hydrides), strong bases (e.g. sodium hydroxide).

Hazardous Decomposition Products

May include but are not limited to oxides of carbon, nitrogen and ammonia.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure

Inhalation.

Skin contact.

Skin absorption.

Eye contact.

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Hydrotreated kerosene	> 6.03 mg/L (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 2000 mg/kg (rabbit)
2-Butoxyethanol	450 ppm (rat) (4-hour exposure)	530 mg/kg (rat)	400-500 mg/kg (rabbit)
Coconut Diethanolamide		> 3000 mg/kg (rat)	> 2000 mg/kg (rabbit)
Alcohols, C9-11, ethoxylated,		1378 mg/kg (rat)	> 2000 mg/kg (rabbit)

Product Identifier: Oust V.O.C. Compliant - Ver. 1

SDS No.: 0800

Date of Preparation: November 13, 2024

Date of Last Revision:

Page 04 of 07

liquids			
Naphtha (petroleum), hydrotreated light	> 23 mg/L (rat) (4-hour exposure)	> 5800 mg/kg (rat)	> 2920 mg/kg (rabbit)

Skin Corrosion/Irritation

May cause irritation or symptoms such as redness, edema, drying, defatting or cracking of the skin.

Serious Eye Damage/Irritation

May cause severe irritation or burns.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the respiratory system.

Skin Absorption

May cause irritation on prolonged contact.

Ingestion

Harmful if swallowed.

Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

No chronic effects are expected provided adequate person protection is taken during usage.

Respiratory and/or Skin Sensitization

Not expected to produce any respiratory system problems when used in a well ventilated area.

Carcinogenicity

Not known to cause cancer.

Reproductive Toxicity

Development of Offspring

Not known to harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Effects on or via Lactation

Not known to cause effects on or via lactation.

Germ Cell Mutagenicity

Not known to be a mutagen.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

May cause long-term adverse effects in the aquatic environment.

Persistence and Degradability

May cause long-term adverse effects in the aquatic environment.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	1268	Petroleum Distillates, N.O.S.	3	III

Product Identifier: Oust V.O.C. Compliant - Ver. 1

SDS No.: 0800

Date of Preparation: November 13, 2024

Date of Last Revision:

Page 06 of 07

Special Precautions Please note: May be shipped as a Limited Quantity when transported in containers no larger than 5 litres in packages not exceeding 30 kg gross mass.

Transport in Bulk according to International Maritime Organization Instruments

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

USA

Toxic Substances Control Act (TSCA) Section 8(b)

Listed on the TSCA Inventory.

SECTION 16. OTHER INFORMATION

SDS Prepared By Mark Bryans

Phone No. (905) 648-7832 ext 351

Date of Preparation November 13, 2024

Disclaimer To the best of our knowledge, the information contained herein is accurate. However, the user of this product assumes all risks and responsibilities relating to the use of this product. No representation of warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or product to which the information refers.

Product Identifier: Oust V.O.C. Compliant - Ver. 1

SDS No.: 0800

Date of Preparation: November 13, 2024

Date of Last Revision:

Page 07 of 07