

Safety Data Sheet

Gator Skin Auto Body Rubberized Undercoating Spray Aerosol

SECTION 1. IDENTIFICATION

Product Identifier	Gator Skin Auto Body Rubberized Undercoating Spray Aerosol
Other Means of Identification	Code No. A847
Recommended Use	Rubberized Coating.
Restrictions on Use	Use only as directed according to label instructions.
Manufacturer/Supplier Identifier	Leysons Products, a division of 1787528 Ontario Inc., 1366 Sandhill Drive, Ancaster, Ontario, L9G 4V5, (905) 648-7832
Emergency Phone No.	Mark Bryans, (905) 648-7832 ext 351, Monday to Friday, 8:00 AM to 3:30 PM
	CANUTECH, 613-996-6666, 24-hr for Emergencies involving Dangerous Goods
SDS No.	0592

SECTION 2. HAZARD IDENTIFICATION

Classification

Flammable aerosol - Category 1; Gas under pressure - Compressed gas; Skin irritation - Category 2; Eye irritation - Category 2A; Respiratory sensitization - Category 1B; Carcinogenicity - Category 1A; Specific target organ toxicity (repeated exposure) - Category 2

Label Elements



Danger

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Causes skin and eye irritation.

May cause damage to organs through prolonged or repeated exposure.

Suspected of damaging fertility or the unborn child.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	%	Other Identifiers	Other Names
Acetone	67-64-1	30-60		
n-Butane	106-97-8	15-40		
Propane	74-98-6	10-30		
Toluene	108-88-3	10-30		
Xylene (mixed isomers)	1330-20-7	3-7		

Carbon black	1333-86-4	1-5	
Light aromatic solvent naphtha	64742-95-6	0.1-1.0	

Notes

Concentrations are expressed in % weight/weight.

SECTION 4. FIRST-AID MEASURES

First-aid Measures

Inhalation

If irritation is experienced, remove person to fresh air.

If experiencing respiratory symptoms (e.g. coughing, shortness of breath, wheezing), call a Poison Centre or doctor. **Skin Contact**

IF ON SKIN (or hair), remove all contaminated clothing and launder before reuse.

Rinse skin with plenty of water or shower.

Call a physician if irritation develops or persists.

Eye Contact

Immediately rinse the contaminated eye(s) with lukewarm, gently flowing water for 15-20 minutes, while holding the eyelid(s) open.

Remove contact lenses, if present and easy to do.

If eye irritation persists, get medical advice or attention.

Ingestion

Never give anything by mouth if person is rapidly losing consciousness, or is unconscious or convulsing. Do not induce vomiting.

If vomiting occurs naturally, lie on your side in the recovery position. Rinse mouth with water again.

Immediately call a Poison Centre or doctor.

Most Important Symptoms and Effects, Acute and Delayed

May irritate the respiratory system. May cause severe eye irritation or burns. May cause skin irritation on prolonged contact. Harmful if swallowed.

Immediate Medical Attention and Special Treatment

Target Organs

Eyes, skin, respiratory system.

Medical Conditions Aggravated by Exposure

Asthma, skin allergies.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Carbon dioxide, dry chemical powder or appropriate foam.

Unsuitable Extinguishing Media

Water.

Specific Hazards Arising from the Product

Extremely flammable liquid and vapour. Can ignite at room temperature. Releases vapour that can form explosive mixture with air.

Special Protective Equipment and Precautions for Fire-fighters

Containers may explode if heated.

Wear full fire fighting equipment and self contained breathing apparatus. Fire-fighters may enter the area if positive pressure SCBA and full Bunker Gear is worn.

Product Identifier:	Gator Skin Auto Body Rubberized Undercoating Spray Aerosol - Ver. 1	SDS No.:	0592
Date of Preparation:	October 07, 2020		
Date of Last Revision:		Page	02 of 06

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures

Increase ventilation to area or move leaking container to a well-ventilated and secure area.

Eliminate all ignition sources. Use grounded, explosion-proof equipment.

Wear protective gloves and eye protection as a precaution.

Wear a NIOSH approved air-purifying respirator with an organic vapour cartridge.

Environmental Precautions

Do not allow into any sewer, on the ground or into any waterway. If the spill is inside a building, prevent product from entering drains, ventilation systems and confined areas. Minimize the use of water to prevent environmental contamination.

Methods and Materials for Containment and Cleaning Up

Place used absorbent into suitable, covered, labelled containers for disposal.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling

Do not get in eyes, on skin or on clothing.

Do not spray on an open flame or other ignition source. Do not pierce or burn container, even after use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing in this product.

Wear gloves and eye protection as a precaution.

Wear a NIOSH approved air- purifying respirator with an organic vapour cartridge.

Conditions for Safe Storage

Store in a cool dry area away from incompatible materials.

Keep out of reach of children in a tightly closed container away from food, drink and animal feed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

	ACGIH	ITLV®	OSH	A PEL	AIHA V	VEEL
Chemical Name	TWA	STEL	TWA	Ceiling	8-hr TWA	TWA
Propane	1800 mg/m3					
n-Butane		1000 ppm				
Acetone	250 ppm		1000 ppm			
Toluene	20 ppm		100 ppm			
Xylene (mixed isomers)	100 ppm	150 ppm				
Carbon black	7 mg/m3					
Light aromatic solvent naphtha	21 ppm					

Appropriate Engineering Controls

Use ventilation adequate to keep exposures (airborne levels of vapour) below the recommended exposure limits.

Individual Protection Measures

Eye/Face Protection

Wear chemical safety goggles and face shield when contact is possible.

Skin Protection

Wear protective gloves and clothing to prevent skin contact.

Respiratory Protection

Use in well ventilated areas. In case of insufficient ventilation, wear a NIOSH approved air-purifying respirator with an organic vapour cartridge.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Basic Physical and Chemical Properties

Basic Physical and Chemical I	Properties
Appearance	Black.
Odour	hydrocarbon odor
Odour Threshold	Not available
рН	Not applicable
Melting Point/Freezing Point	Not available (melting); Not available (freezing)
Boiling point/Initial boiling point	Not available
Boiling Range	Not available
Flash Point	~ -104 °C (-155 °F)
Evaporation Rate	> 1
Flammability (solid, gas)	Not available
Upper/Lower Flammability or Explosive Limit	Not available (upper); Not available (lower)
Vapour Pressure	Not available
Vapour Density (air = 1)	> 1
Relative Density (water = 1)	Not available
Solubility	Not applicable in water; Not available (in other liquids)
Partition Coefficient, n- Octanol/Water (Log Kow)	Not available
Auto-ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	Not available (kinematic); Not available (dynamic)
Other Information	
Other Physical Property 1	Not available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions of use. **Chemical Stability**

Normally stable.

Conditions to Avoid

High temperatures. Freezing. Incompatible materials.

Incompatible Materials

Strong acids (e.g. hydrochloric acid), strong oxidizing agents (e.g. perchloric acid), strong reducing agents (e.g. hydrides).

Hazardous Decomposition Products

May include but are not limited to oxides of carbon, nitrogen and ammonia.

SECTION 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure Inhalation. Skin contact. Skin absorption. Eye contact.

Product Identifier: Gator Skin Auto Body Rubberized Undercoating Spray Aerosol - Ver. 1 SDS No.: 0592 Date of Preparation: October 07, 2020

Page 04 of 06

Ingestion.

Acute Toxicity

Chemical Name	LC50	LD50 (oral)	LD50 (dermal)
Propane	658 mg/L (rat) (4-hour exposure) (gas)		
n-Butane	658,000 mg/L (rat) (4-hour exposure) (vapour)		
Acetone		5,800 mg/kg (rat)	
Toluene	28.1 mg/L (rat) (4-hour exposure)	> 5000 mg/kg (rat)	> 5000 mg/kg (rabbit)
Xylene (mixed isomers)		4300 mg/kg (rat)	
Carbon black		> 8,000 mg/kg (rat)	
Light aromatic solvent naphtha		5,000 mg/kg (rat)	

Skin Corrosion/Irritation

May cause irritation or symptoms such as redness, edema, drying, defatting or cracking of the skin.

Serious Eye Damage/Irritation

May cause serious eye irritation based on information for closely related materials.

STOT (Specific Target Organ Toxicity) - Single Exposure

Inhalation

May cause irritation of the respiratory system.

Skin Absorption

May cause irritation on prolonged contact.

Ingestion

Harmful if swallowed.

Aspiration Hazard

May be drawn into the lungs (aspirated) if swallowed or vomited.

STOT (Specific Target Organ Toxicity) - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

Respiratory and/or Skin Sensitization

Not expected to produce any respiratory system problems when used in a well ventilated area.

Carcinogenicity

Not known to cause cancer.

Reproductive Toxicity

Development of Offspring

May harm the unborn child.

Sexual Function and Fertility

Not known to cause effects on sexual function or fertility.

Effects on or via Lactation

Not known to cause effects on or via lactation.

Germ Cell Mutagenicity

No information was located.

Interactive Effects

No information was located.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

May cause long-term adverse effects in the aquatic environment.

Persistence and Degradability

May cause long-term adverse effects in the aquatic environment.

Bioaccumulative Potential

No information was located.

Mobility in Soil

No information was located.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents and container in accordance with local, regional, national and international regulations.

SECTION 14. TRANSPORT INFORMATION

Regulation	UN No.	Proper Shipping Name	Transport Hazard Class(es)	Packing Group
Canadian TDG	1950	Aerosols, Flammable	2.1	Not applicable.

Special Precautions Please note: This product meets the exemption requirements and may be shipped as a "Limited Quantity".

Transport in Bulk according to International Maritime Organization Instruments

Not applicable

SECTION 15. REGULATORY INFORMATION

Safety, Health and Environmental Regulations

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all of the information required by the Controlled Products Regulations.

SECTION 16. OTHER INFORMATION

SDS Prepared By	Mark Bryans
Phone No.	(905) 648-7832 ext 351
Date of Preparation	October 07, 2020
Disclaimer	To the best of our knowledge, the information contained herein is accurate. However, the user of this product assumes all risks and responsibilities relating to the use of this product. No representation of warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to the information or product to which the information refers.

Product Identifier:Gator Skin Auto Body Rubberized Undercoating Spray Aerosol - Ver. 1SDS No.:0592Date of Preparation:October 07, 2020Page06 of 06

