SAP REMOVER

NEW V.O.C. COMPLIANT

SAP AND ORGANIC RESIN REMOVER

PRODUCT CODE: 180

DESCRIPTION AND PRODUCT BENEFITS:

SAP REMOVER is a quick-drying formula that penetrates, lifts, and dissolves sap and organic resins. If any sap is detected on a vehicle's paint surface, it should be removed promptly with SAP REMOVER to ensure no etching or discolouring occurs to the paint's clear coat.

DIRECTIONS OF USE AND APPLICATION:

1. Preclean vehicle using a Vehicle Wash Soap and dry. 2. Apply SAP REMOVER to a clean microfiber towel or terry cloth. 3. Place the cloth with SAP REMOVER on the top of the desired area. 4. Let the cloth sit for at least 30 seconds. 5. Rub the area until the sap is gone. 6. For stubborn areas, retreat surface, repeating steps 2 to 5.

PRECAUTIONS:

Test all surfaces in an inconspicuous area. Do not mix with other chemicals. Keep from freezing. Flammable, keep away from open flames, hot surfaces, or sources of ignition.

HEALTH & SAFETY INFORMATION:

For further information on the safe handling, storage and precautions for use of this product, consult the Safety Data Sheet. Keep out of reach of children.

DISCLAIMER:

As the actual conditions of use are out of our control no liability is accepted for any loss or damage caused directly or indirectly through the use of our products. Intending users should satisfy themselves, by carrying out appropriate tests, as to the suitability of this product for any particular purpose.

TYPICAL DATA:

APPEARANCE: Clear light blue liquid.
SPECIFIC GRAVITY: ~ 0.81 g/ml
ODOUR: Slight solvent odour.
SOLUBILITY: Completely water soluble.
VISCOSITY: Water thin.
FLASH POINT: 12°C

AVAILABLE SIZES:

BOTTLE

A18010 - **BOTTLE** - 946 ML / 1 US QUART

PROUDLY CANADIAN

autovalet.ca

Auto Valet is a registered trademark. © Leysons Products