

KNOCK OUT

LIQUID FALLOUT REMOVER

PRODUCT CODE: 306

DESCRIPTION AND PRODUCT BENEFITS:

KNOCK OUT effectively removes industrial fallout such as rail dust and smokestack fly ash. When used with care, KNOCK OUT dissolves the minute iron particles which are embedded in painted surfaces. KNOCK OUT is formulated with mild organic acids, which are safe on glass and paint.

DIRECTIONS OF USE AND APPLICATION:

1. Wet the painted area of application with cool water. 2. Spray undiluted KNOCK OUT on the painted area of application. 3. Allow KNOCK OUT to crystallize on the painted surface, approximately 5 to 10 minutes, depending on relative humidity. 4. Rinse the area thoroughly with a high-pressure washer. 5. For stubborn particles, retreat areas, repeating steps 2 to 4. 6. Wash vehicle using a Vehicle Wash Soap, to allow for final neutralization and particle removal.

PRECAUTIONS:

Apply to a cool surface only. Do not apply in direct sunlight. Do not mix with other chemicals. Keep from freezing.

HEALTH & SAFETY INFORMATION:

For further information on the safe handling, storage and precautions for use of this product, consult the Safety Data Sheet. Keep out of reach of children.

DISCLAIMER:

As the actual conditions of use are out of our control no liability is accepted for any loss or damage caused directly or indirectly through the use of our products. Intending users should satisfy themselves, by carrying out appropriate tests, as to the suitability of this product for any particular purpose.



TYPICAL DATA:

APPEARANCE: Clear yellow liquid.

SPECIFIC GRAVITY: ~1.03 g/ml

ODOUR: Fruity.

PH: <1.0

SOLUBILITY: Completely water soluble.

% NON-VOLATILE: ~9.5

VISCOSITY: Water thin.

AVAILABLE SIZES:



A30612 - **JUG** - 3.78 L / 1 US GAL
 A30614 - **CUBE** - 18.9 L / 5 US GAL
 A30618 - **DRUM** - 208.2 L / 55 US GAL
 BA306 - **WORKPLACE LABEL**

